Product: Prolong Aluminium Liquid "A" Page 1 of 6

Date of Issue: March 2021

Hazardous according to criteria of Worksafe Australia

PRODUCT & COMPANY UNDERTAKING IDENTIFICATION

Product Name: PROLONG ALUMINIUM LIQUID "A"

Product Code: 95053A

Major Recommended Use: Metal repair composite when mixed with "B".

Company: Peerless Industrial Systems Pty Ltd

ABN: 14 097 615 391

Address: PO Box 407 Cloverdale WA 6985 AUSTRALIA

Telephone Number: 61 (08) 9477 3788 Fax Number: 61 (08) 9477 3766

Email: service@peerlessindustrialsystems.com

Emergency Telephone Number: 13 11 26

HAZARDS IDENTIFICATION

GHS Classification

2

Skin corrosion / irritation:

Serious eye damage / eye irritation:

Category 2

Category 2

Category 1

Chronic aquatic toxicity:

Category 2

GHS Label Element

Hazard pictograms:





Signal Word: Warning

Hazard statements: H315 Causes skin irritation.

H317 May cause allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements: P102 Keep out of reach of children

P103 Read label before use

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear eye/face protection, gloves, protective clothing.

Response statements: P101 If medical advice is needed, have product container or label at hand

P302 + P352 IF ON SKIN: Wash with soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Poison Schedule (Australia) S5

Other hazards which do not result in classification

None known.

Product: Prolong Aluminium Liquid "A" Page 2 of 6

Date of Issue: March 2021

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS Number Proportion

Epoxy Resin 25068-38-6 <40%

Ingredients determined not to be hazardous not applicable to 100%

4 FIRST AID MEASURES

General advice: Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled: Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact: Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact: Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed: Clean mouth with water and drink afterwards plenty of water.

DO NOT induce vomiting and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms:

and effects, both acute and

delayed.

irritant effects sensitising effects

Allergic reactions

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects and symptoms.

Causes skin irritation

May cause allergic skin reaction Causes serious eye irritation

Notes to physician: Treat symptomatically.

5 FIRE FIGHTING MEASURES

Suitable extinguishing media: Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Specific hazards during fire

fighting:

Do not allow run-off from firefighting to enter drains or water courses.

Hazardous combustion: No

products:

No hazardous combustion products are known.

Specific extinguishing methods: Collect contaminated fire extinguishing water separately. This must not be discharged

to drains.

Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

Special protective equipment: In the event of fire, wear self-contained breathing apparatus.

Product: Prolong Aluminium Liquid "A" Page 3 of 6

Date of Issue: March 2021

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions: Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up:

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust).

Keep in suitable, closed containers for disposal.

7 HANDLING & STORAGE

Advice on protection against fire and explosion:

Normal measures for preventive fire protection.

Advice on safe handling:

Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which a

mixture is being used.

Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of the workday.

Conditions for safe storage: Keep c

Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent

leakage.

Store in accordance with local regulations.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection: Use respiratory protection unless adequate local exhaust ventilation is provided or

exposure assessment demonstrates that exposures are within recommended

exposure guidelines.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/ vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing

apparatus must be used.

Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates it is

necessary.

Eye protection: Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary.

Product: Prolong Aluminium Liquid "A" Page 4 of 6

Date of Issue: March 2021

Skin and body protection: Choose body protection in relation to its type, to the concentration and amount of

dangerous substances, and to the specific workplace.

9 PHYSICAL & CHEMICAL PROPERTIES

Appearance: Thick Liquid

Colour: Grey

Odour: None discernible
Odour Threshold: Not available

pH: 7

Melting Point:

Boiling Point (@760mm Hg):

Not available > 230°C

Flashpoint (°C): > 200°C Closed Cup
Evaporation rate: No data available
Flammability: Not applicable
Upper explosion limit: Not available
Lower explosion limit: Not available
Vapour Pressure (mm Hg): 3.9 @ 20°C
Relative Vapour Density: Not available

Density: 2.2

Solubility in Water:

Partition Coefficient n-Octanol/Water

Auto-ignition temperature:

Decomposition temperature:

Per cent Volatiles:

Volatile Organic Compounds:

Insoluble

Not available

Not available

< 0.5%

< 0.5%

10 STABILITY & REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: The product is chemically stable.

Possibility of hazardous reactions: Stable under recommended storage conditions.

Conditions to avoid: Heat and sources of ignition.

Incompatible materials: Strong oxidizing materials.

11 TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic skin reaction. Category 2 Hazard (irritant to skin). Category 1A Hazard (skin sensitiser).

Eye contact: Causes serious eye irritation. Category 2A Hazard (reversible effects to eyes)

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Acute toxicity: Not classified based on available information.

Chronic toxicity:

Germ cell mutagenicity:Not classified based on available information.

Product: Prolong Aluminium Liquid "A" Page 5 of 6

Date of Issue: March 2021

Carcinogenicity: Not classified based on available information.

Reproductive toxicity:Not classified based on available information.

STOT – single exposure: Not classified based on available information.

STOT – repeated exposure: Not classified based on available information.

Aspiration toxicity: Not classified based on available information.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects

Product:

Additional ecological information: Avoid contaminating waterways or discharging to sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues: The product should not be allowed to enter drains, water courses

or the soil.

Do not contaminate ponds, waterways or ditches with chemical or

used container.

Send to a licensed waste management company.

Contaminated packaging: Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

14 TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. UN 3082

Proper Shipping Name: Environmentally hazardous substance, liquid, N.O.S.

Class: 9
Packing group: III
Labels: 9
Packing instruction (cargo aircraft): 964
Packing instruction (passenger 964

aircraft):

IMDG-Code

UN number: UN 3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class: 9
Packing group: III
Labels: 9

Product: Prolong Aluminium Liquid "A" Page 6 of 6

Date of Issue: March 2021

EmS Code: F-A, S-F

Marine pollutant: This material is classified as a Marine Pollutant (P) according to the

International Maritime Dangerous Goods Code

Road & Rail Transport

"Australian Code for the Transport of Dangerous Goods by Road & Rail"

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in packaging, IBC's or any other receptacles not exceeding 500 Kg (L).

15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture.

Standard for the Uniform Scheduling Schedule 5 of Medicines and Poisons:

International Chemical Weapons Convention (CWC) Not applicable

Schedules of Toxic Chemicals and Precursors

Prohibition / Licensing Requirements: There is no applicable prohibition or notification / licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS: On the inventory, or in compliance with the inventory.

16 OTHER INFORMATION

Date format: September 2020

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: www.epigen.com.au

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material