Product: Prolong Synthetic Rubber Putty "A" Page 1 of 6 Date of Issue: March 2021

Hazardous according to criteria of Worksafe Australia 1 **PRODUCT & COMPANY UNDERTAKING IDENTIFICATION** PROLONG SYNTHETIC RUBBER PUTTY "A" Product Name: Product Code: 95070A Major Recommended Use: Synthetic Elastomer when mixed with "B". Peerless Industrial Systems Pty Ltd Company: ABN: 14 097 615 391 Address: PO Box 407 Cloverdale WA 6985 AUSTRALIA Telephone Number: 61 (08) 9477 3788 Fax Number: 61 (08) 9477 3766 service@peerlessindustrialsystems.com Email: Emergency Telephone Number: 13 11 26

2 HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity – Oral
Serious Eye Damage/Irritation
Toxic to Reproduction
Specific Target Organ Toxicity
(Repeated Exposure)

Category 4 Category 2A Category 1B Category 2

GHS Label Element

Hazard pictograms:



Signal Word:	Danger
Hazard statements:	H302 Harmful if swallowed. H319 Causes serious eye irritation. H360 May damage fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements:	 P102 Keep out of reach of children. P103 Read label before use. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust, fume, gas, mist, vapours or spray. P264 Wash hands, face and all exposed skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P281 Use personal protective equipment as required.
Response statements:	 P101 If medical advice in needed, have product container or label on hand. P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. P305+P351+P338 IF IN ETES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell. P330 Rinse mouth. P337+P313 If eye irritation persists: Get medical advice/attention.
Storage:	P405 Store locked up.
Disposal:	P501 Dispose of contents/ container to an approved waste disposal plant.

Product: Prolong Synthetic Rubber Putty "A" Page 2 of 6

Date of Issue: March 2021

Poison Schedule (Australia) Not Applicable

Other hazards which do not result in classification: None known.

3 COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical Name	CAS Number	Proportion	
1,3-Benzenediamine, 2(or 4)-methyl-4,6(or 2,6) -bis(methylthio)-	106264-79-3	<10%	
Ingredients determined not to be hazardous	not applicable	to 100%	

4 FIRST AID MEASURES

General advice:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled:	Move to fresh air.
In case of skin contact:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed:	Clean mouth with water and drink afterwards plenty of water. DO NOT induce vomiting and call a physician.
Most important symptoms: and effects, both acute and delayed.	irritant effects sensitising effects Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms. May cause allergic skin reaction
Notes to physician:	Treat symptomatically.

5 FIRE FIGHTING MEASURES

Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Specific hazards during fire fighting:	Do not allow run-off from firefighting to enter drains or water courses.	
Hazardous combustion: products:	No hazardous combustion products are known.	
Specific extinguishing methods:Collect contaminated fire extinguishing water separately. This must not be discharged to drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.		
Special protective equipment:	In the event of fire, wear self-contained breathing apparatus.	

Product: Prolong Synthetic Rubber Putty "A" Page 3 of 6

Date of Issue: March 2021

6 ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures:	Use personal protective equipment. Deny access to unprotected persons.	
Environmental precautions:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.	
Methods and materials for containment and cleaning up:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
7 HANDLING & STORAGE		
Advice on protection against fire and explosion:	Normal measures for preventive fire protection.	

Advice on safe handling:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which a mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of the workday.
Conditions for safe storage:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters Contains no substances with occupational exposure limit values.

Personal protective equipment

i oroonar protoonro oquipi	
Respiratory protection:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/ vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates it is necessary.
Eye protection:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Product: Prolong Synthetic Rubber Putty "A" Page 4 of 6 Date of Issue: March 2021

Skin and body protection:

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific workplace.

9 PHYSICAL & CHEMICAL PROPERTIES

Appearance: Colour: Odour: Odour Threshold: pH: Melting Point: Boiling Point (@760mm Hg): Flashpoint (°C): Evaporation rate: Flammability: Upper explosion limit: Lower explosion limit: Lower explosion limit: Vapour Pressure (mm Hg): Relative Vapour Density: Density: Solubility in Water: Solubility in Mater: Solubility in n-Octanol: Partition Coefficient n-Octanol/Water Auto-ignition temperature:	Liquid Light Amber Not available Not available Alkaline Not available > 305°C > 200°C Closed Cup No data available Not applicable Not available Not available < 10 @ 20°C Not available 1.1 Slight (0.1-2.5%) Complete (100%) No data Not available
Solubility in n-Octanol:	Complete (100%)
Auto-ignition temperature: Decomposition temperature: Per cent Volatiles: Volatile Organic Compounds:	Not available Not available <0.5% <0.5%

10 STABILITY & REACTIVITY	
Reactivity:	No dangerous reaction known under conditions of normal use.
Chemical stability:	The product is chemically stable.
Possibility of hazardous reactions:	Stable under recommended storage conditions.
Conditions to avoid:	Not applicable.
Incompatible materials:	Mineral acids, Organic acids, Oxidising agents, Reactive metals, Sodium or Calcium Hypochlorite.
Hazardous Decomposition Products:	Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides, in a fire.
Hazardous Transformation Products:	Will not occur.

11 TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Skin contact :	A skin sensitiser. Repeated or prolonged skin contact may lead to allergic skin reaction. Category 2 Hazard (irritant to skin). Category 1A Hazard (skin sensitiser).
Eye contact:	Causes serious eye irritation. Category 2A Hazard (reversible effects to eyes)
Ingestion:	Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract
Inhalation:	Material may be an irritant to mucous membranes and respiratory tract.

Product: Prolong Synthetic Rubber Putty "A" Page 5 of 6 Date of Issue: March 2021

Acute toxicity: Not classified based on available information.

Chronic toxicity:	
Germ cell mutagenicity:	Not classified based on available information.
Carcinogenicity:	Not classified based on available information.
Reproductive toxicity:	Not classified based on available information.
STOT – single exposure:	Not classified based on available information.
STOT – repeated exposure:	Not classified based on available information.
Aspiration toxicity:	Not classified based on available information.

12 ECOLOGICAL INFORMATION	
Ecotoxicity:	No data available.
Persistence and degradability:	No data available.
Bioaccumulative potential:	No data available.
Mobility in soil:	No data available.

Other adverse effects

Product:

Additional ecological information: Avoid contaminating waterways or discharging to sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS	
Disposal methods Waste from residues:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

14 TRANSPORT INFORMATION

ADG Shipping Data: Not regulated. IMDG Shipping Data: Not regulated. ICAO/IATA Shipping Data: Not Regulated

15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture. Standard for the Uniform Scheduling Schedule 5

of Medicines and Poisons:

Product: Prolong Synthetic Rubber Putty "A" Page 6 of 6 Date of Issue: March 2021

Schedules of Toxic Chemicals and Precursors

Prohibition / Licensing Requirements: There is no applicable prohibition or notification / licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS:

On the inventory, or in compliance with the inventory.

16 OTHER INFORMATION

Date format:

24 June 2021

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: <u>www.epigen.com.au</u>

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material